

検査成績表

<TEST REPORT>

1/2

品名<Model Name> (パワーハイテスタ<POWER HiTESTER>)
 形名<Model Number> (3332)
 製造番号<Serial No.> (No.)
 検査年月日<Test Date> (<YYYY-MM-DD>)
 検査条件<Test Conditions> (°C, %rh)
 検査周波数<Test Frequency> (55 Hz)

項目 <Item>	レギュレイトド/レスポンス <RECT> <RESP>	レンジ <Range>	入力 <Input>	許容範囲 <Tolerance>	表示値 <Indicated Value>
確度<Accuracy>					
	RMS	FAST	600 V	600.00 V	598.80 V ~ 601.20 V (V)
			300 V	300.00 V	299.40 V ~ 300.60 V (V)
			150.00 V	149.55 V	~ 150.45 V (V)
			30.00 V	29.67 V	~ 30.33 V (V)
			0.00 V	-0.30 V	~ 0.30 V (V)
			150 V	150.00 V	149.70 V ~ 150.30 V (V)
			60 V	60.000 V	59.880 V ~ 60.120 V (V)
			30 V	30.000 V	29.940 V ~ 30.060 V (V)
			15 V	15.000 V	14.970 V ~ 15.030 V (V)
	MEAN		300 V	300.00 V	299.40 V ~ 300.60 V (V)
	MEAN+FILT		300.00 V	300.00 V	299.40 V ~ 300.60 V (V)
	RMS	SLOW	300.00 V	300.00 V	299.40 V ~ 300.60 V (V)
	RMS	FAST	50 A	20.000 A	19.930 A ~ 20.070 A (A)
			20 A	20.000 A	19.960 A ~ 20.040 A (A)
			10 A	10.000 A	9.980 A ~ 10.020 A (A)
			5 A	5.0000 A	4.9900 A ~ 5.0100 A (A)
				2.5000 A	2.4925 A ~ 2.5075 A (A)
				0.5000 A	0.4945 A ~ 0.5055 A (A)
				0.0000 A	-0.0050 A ~ 0.0050 A (A)
			2 A	2.0000 A	1.9960 A ~ 2.0040 A (A)
			1 A	1.0000 A	0.9980 A ~ 1.0020 A (A)
			0.5 A	500.00 mA	499.00 mA ~ 501.00 mA (mA)
			0.2 A	200.00 mA	199.60 mA ~ 200.40 mA (mA)
			0.1 A	100.00 mA	99.80 mA ~ 100.20 mA (mA)
			50 mA	50.000 mA	49.900 mA ~ 50.100 mA (mA)
			20 mA	20.000 mA	19.960 mA ~ 20.040 mA (mA)
			10 mA	10.000 mA	9.980 mA ~ 10.020 mA (mA)
			5 mA	5.0000 mA	4.9900 mA ~ 5.0100 mA (mA)
			2 mA	2.0000 mA	1.9960 mA ~ 2.0040 mA (mA)
			1 mA	1.0000 mA	0.9980 mA ~ 1.0020 mA (mA)
		SLOW	5 A	5.0000 A	4.9900 A ~ 5.0100 A (A)
<PEAK>		FAST	5 A	7.071A (PEAK)	6.734 A ~ 7.408 A (A)

総合判定<Overall Result>

()

検査者<Inspected by>

()

承認者<Approved by>

()

検査成績表

<TEST REPORT>

2/2

製造番号<Serial No.> (No.)
 検査年月日<Test Date> (1900-01-00)
 <YYYY-MM-DD>

項目 <Item>	レギュレイト レスポンス		レンジ <Range>		入力 <Input>			許容範囲 <Tolerance>			表示値 <Indicated Value>	
	<RECT>	<RESP>	電圧 <U>	電流 <I>	電圧 <U>	電流 <I>	電力 <P>					
確度<Accuracy>												
	RMS	FAST	150V	5A	150V	5A	750W	748.50 W	~	751.50 W	(W)
					150V	2.5A	375W	373.88 W	~	376.12 W	(W)
					150V	0.5A	75W	74.18 W	~	75.82 W	(W)
					0V	0A	0W	-0.75 W	~	0.75 W	(W)
		SLOW	150V	5A	150V	5A	750W	748.50 W	~	751.50 W	(W)

項目 <Item>	レンジ <Range>		入力 <Input>		許容範囲 <Tolerance>			表示値 <Indicated Value>	
	電圧 <U>	周波数 <FREQ>	電圧 <U>	周波数 <FREQ>					
周波数 <Frequency>	300V	500Hz	300V	55.000Hz	54.944 Hz	~	55.056 Hz	(Hz)
	5A	500Hz	5A	55.000Hz	54.944 Hz	~	55.056 Hz	(Hz)

備考<Note>

FAIL判定箇所は、グレー表示としています。<FAIL decision points are highlighted in gray.>